

v5WP



Get your POS solution now at



1300 888 POS op-tech.com.au

point of sale system $\,\cdot\,$ security system $\,\cdot\,$ business intelligence



Removable SSD*



Aluminium Die-cast Sleek Enclosure



IP54 Whole Unit



Senor v5WP Series Intelligent Touch POS Terminal

Senor v5WP Series is designed to meet the functional requirements of the users as well as having the modern appeal to enhance varied ambiences of the operating environment.






The design concept complements a user's workflow and operation of the POS unit thereby increasing productivity and efficiency. A variety of POS peripherals is available, including optional customer display screen and tool free interchangeable coloured bezel.

With its **elegant design**, v5WP is ideally suited for the retail and hospitality industries' flagship and pop-up stores.

I/O Connector



v5WP J19

2 x DB9 | 1 x Cash Drawer | 4 x USB 1 x LAN | 1 x VGA




v5WP X35

2 x DB9 | 1 x Cash Drawer | 6 x USB 2 x LAN | 1 x VGA



Features





Internal Power Supply Cable Management System



Fanless / Ventless / Screwless

^{*} Coloured units are for special order only.



SPECIFICATIONS	v5WP J64	v5WP X35
PROCESSOR	Intel Celeron Quad Core J6412 1.5 GHz (Turbo Boost up to 2.6 GHz)	Intel Dual Core i3-6100U 2.3 GHz (with Intel HT)
SYSTEM MEMORY	4 GB DDR3L RAM (up to 8 GB)	4 GB DDR4 RAM (up to 32 GB)
STORAGE DEVICE	2 x M.2 SATA SSD	2 x Half Slim removable SATA SSD (up to 240 GB, supports RAID)
DISPLAY		
SIZE / RESOLUTION	15" TFT LCD (LED backlight) / 1024 x 768 pixels	
BRIGHTNESS	350 cd/m ²	
TOUCH SCREEN PANEL	Projected capacitive touch	
I/O INTERFACE		
USB PORT	4 x USB 2.0	6 x USB 2.0
SERIAL PORT	2 x DB9	
VIDEO PORT	1 x VGA	
AUDIO PORT	2 x built-in speakers / 1 x 3.5 mm mic in/line out	
CASH DRAWER PORT	1 x RJ12 (24 V)	
ETHERNET PORT	1 x RJ45 10/100/1000 Mbps	2 x RJ45 10/100/1000 Mbps
OPERATING SYSTEM		
WINDOWS	10 IoT / 10 Pro	
ENVIRONMENT & MECHANICAL S	SPECIFICATIONS	
DIMENSIONS & WEIGHT	366 (W) x 495 (H) x 245 (D) mm 10 kg	
CHASSIS MATERIAL	Die-cast aluminium	
IP RATING	IP54 whole unit	
TEMPERATURE	Operating: 0°C to 40°C Storage: -20°C to 60°C	
HUMIDITY	Operating: 0% to 80% Storage: 10% to 90% (non-condensing)	
POWER CONSUMPTION	24 V / 5 A, internal power adaptor, 100-240 V, 50/60 Hz	
MODEL OPTIONS		
INTEGRATED CARD READERS	3-track MSR, RFID (125 kHz, 13.56 MHz), IC card reader	
CUSTOMER DISPLAY	VFD / 7" LCD / 10" LCD / 15" LCD	
INTEGRATED BARCODE READER	1D/2D barcode reader	
WIRELESS LAN	Integrated 802.11 b/g/n/ac + Bluetooth 4.1	
COLOURED FRAME	Black (standard) White / Red / Green / Purple / Teal Blue (special order)	
COLOURED UNIT	Black (standard) Silver (special order)	

ALL PRODUCT SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The Senor Building

65 & 67 Weaver Street Coopers Plains QLD 4108, Australia www.senortech.com.au P: +61 7 3275 5888 sales@senortech.com.au



Quality. Safety. Versatility.